



# SEVERE DUTY REELS

## from ALEMITE

Whether you're servicing equipment at a heavy-construction site or remote mine, you need a reel tough enough to stand up to your rugged work conditions—and mobile enough to go virtually anywhere.

These reels include all the advantages found in Alemite's existing line of HEAVY-DUTY REELS—plus added features to deliver durability under the most rigorous uses.

### HIGH PRESSURE (GREASE)

### MAX. REEL PRESSURE 6000 PSI

MODEL	HOSE REEL	DELIVERY HOSE	CONNECTING HOSE	SWIVEL	90° UNION	WGT.
8078-G	7334-C	317874-50	317876-2	331107	1001-86	61 lbs.

DELIVERY HOSE NO.	COUPLING SIZE & THREAD	HOSE ID	MAX. WORK* PRESSURE (PSI)	MIN. BURST PRESSURE (PSI)	AVAILABLE LENGTH (IN FT.)
317874	3/8" NPTF (m) x 1/4" NPTF (f)	1/4"	8000	20,000	30, 50

\*For grease only

### MEDIUM PRESSURE (OIL)

### MAX. REEL PRESSURE 1500 PSI

MODEL	HOSE REEL	DELIVERY HOSE	CONNECTING HOSE	90° UNION	WGT.
8078-H	7335-C	317813-50	317813-2	1001-88	60 lbs.

DELIVERY HOSE NO.	COUPLING SIZE & THREAD	HOSE ID	MAX. WORK PRESSURE (PSI)	MIN. BURST PRESSURE (PSI)	AVAILABLE LENGTH (IN FT.)
317813	1/2" NPTF (m) x 1/2" NPTF (m)	1/2"	2000	8000	15, 20, 30, 40, 50

### MEDIUM PRESSURE (DIESEL FUEL)

### MAX. REEL PRESSURE 300 PSI

MODEL	HOSE REEL	DELIVERY HOSE	CONNECTING HOSE	90° UNION	HOSE STOP	WGT.
8078-K	7337-C	317868-50	317868-2	1001-1212	339389	71 lbs.

DELIVERY HOSE NO.	COUPLING SIZE & THREAD	HOSE ID	MAX. WORK PRESSURE (PSI)	MIN. BURST PRESSURE (PSI)	AVAILABLE LENGTH (IN FT.)
317868	3/4" NPTF (m) x 3/4" NPTF (m)	3/4"	1250	8000	2, 30, 50, 70

### LOW PRESSURE (AIR & WATER)

### MAX. REEL PRESSURE 300 PSI

MODEL	HOSE REEL	DELIVERY HOSE	CONNECTING HOSE	OUTLET BUSHING	AIR COUPLER	AIR ADAPTER	90° UNION	WGT.
8078-J	7336-C	317803-50	317811-2	339236	328030	328034	1001-88	55 lbs.

ALL OF THE ABOVE MODELS INCLUDE A HOSE STOP (337437).

DELIVERY HOSE NO.	COUPLING SIZE & THREAD	HOSE ID	MAX. WORK PRESSURE (PSI)	MIN. BURST PRESSURE (PSI)	AVAILABLE LENGTH (IN FT.)
317803	1/4" NPTF (m) x 1/4" NPTF (m)	3/8"	200	800	3, 7, 15, 25, 30, 40, 50

## REEL FEATURES:

- Weather-resistant Design Gasket and O-Ring—Seal out water around spring and shaft, protecting internal components from corrosion.
- Heavy-Duty 1/4" Base—Thicker, fully-welded base to ensure off-road stability.
- Removable Rollers—Provides easier cleaning and service, allowing for quick reel maintenance.
- Plated and Sealed Bearings—Reduces torque load on power spring for smooth retraction and durability. Also provides corrosion resistance.
- Narrow Design—For maximum use of available space.  
(20 1/4" H x 7" W x 19" D)

## STANDARD REEL FEATURES:

- Anti-lockout Ratchet
- Power Spring Cassette
- Metal Arbor
- 5-Position Guide Arm
- Rolled Sheave Edge

**DISTRIBUTED BY:**

THESE REELS WERE LAST SIGHTED AT:

Lube Trucks

Mining

Agriculture

Construction Sites

Exterior Applications

**ALEMITE CORPORATION**

7845 Little Avenue

Charlotte, NC 28226

Phone: 704-542-6900

800-822-4579

Fax: 704-542-4650

<http://www.alemite.com>